

SPECIFICATION

ITEM	Open Frame Monitor
MODEL	NOP
PART NUMBER	NOP-190
BUYER	
DATE	APRIL. 10, 2008

APPROVED BY

NEXIO CORPORATION	
DRAWN BY	H.J Kim
CHECKED BY	E.R Bae
APPROVED BY	K.S Kim



Nexio Co., Ltd.

5F, Seong-Woong B/D, 898-3, Jakjun-dong,
Gyeyang-gu, Incheon, Korea

Tel : +82 32 556 9545~7

Fax : +82 32 556 9544

CONTENTS

1. Revision History	-----	3
2. Monitor Characteristics	-----	4,5
3. Touch Characteristics	-----	5
4. Touch Electrical	-----	5
5. Touch Environment	-----	5
6. Touch Controller	-----	6
7. Drawing	-----	Appendix1

1. Revision History

Date	Rev. No	Page	Summary
APR.10,2008	S-080325-001		Approval specification of NOP-190 model was issued first

2. Monitor Mechanical

Panel	Housing	Black powder coated Metal
	Monitor Size (Out line)	19inch : 462.4(w)x396.4(h)x61.5(d)mm
	Display Type	SXGA TFT
	Max. Resolution	1280 x 1024
	Display Colors	16M Colors
	Pixel Pitch	0.294 x 0.294mm
	Brightness	300 cd/m ²
	Contrast Ratio	500 : 1(Typical)
	Viewing Angle (typical)	80°/80°(L/R) & 80°/80°(U/D)
	Display Area	376.32 x301.05mm
Input Signal	Supported Video Signal	VGA (15Pin D-Sub)
Resolution Support	Supported	640 x 350 @ 70 Hz 720 x 400 @ 70 HZ 640 X 480 @ 60Hz ~ 75Hz 832 x 624 @ 75Hz (MAC) 800 x 600 @ 56Hz ~ 75 Hz 1024 X 768 @ 60Hz ~ 75Hz 1280 X 1024 @ 80Hz ~ 70Hz
	Recommended	1280 x 1024@60Hz
Power Consumption	On working	<30 watt (Max.)
	Off	<3 watt
OSD Control	Function	Brightness, Contrast, Position(H/V Position), Clock(Clock, Phase, Use), Color (Color temperature, User Adjustment), Language, Information, OSD(OSD time, H/V position, Use), Auto Adjust
Language		English, French, German, Italian,
Plug & Play		DDC1 / DDC2B
Power Saving		VESA DPMS
Power Supply Adapter	Input	AC 100V~240V, 50~60Hz
	Output	DC 12V / 3.5A
Operating Temperature		0 ~ 50 °C
Storage Temperature		-20 ~ 65 °C
Operating Humidity		10 ~ 95% (Non Condensing)
Weight(Net/Gross)		6.8 / 8.5kg

Standard Accessories		15-PIN VGA cable, AC adapter, Power cord
Options	Front Bezel	Aluminum
Touch Screen		IR
Touch Interface		IR– RS232 or USB
Drawing		Please refer to Appendix 1

3. Touch Characteristics

Input Method	Finger or gloved hand activation
Touch Activation Force	No minimum touch activation force
Position Accuracy	Typical centroid accuracy 2mm
Resolution	4,544 x 3,712
Response Time	Touch : 12.9ms
	Drawing : 23.3ms
Glass	Transmission : 92% Up to 100%
	Thickness : 3.2 mm with anti-vandal
Optics Number	71(h) x 58(v)
Optics cell pitch	5.3mm
Available Object Sizes for Touch	Touch : Ø6mm
	Stylus : Ø7mm
Touch Intensity	Over 60,000,000 single point touch

4. Touch Electrical

Operating Voltage	DC 4.6V ~ DC 5V
Power	0.6W(Current) 120mA at DC 5V
Connector between touch panel and controller	22pin FPC cable

5. Touch Environment

Temperature	Operating -20°C to 85°C
	Storage -40°C to 85°C
Humidity	Operating 20% to 85%
	Storage 0~95%
Relative Humidity	Operating 40°C at 90% RH, Noncondensing
Altitude Operating	3,000m
Interface	RS232(C) or USB 1.1
Detection Method	Infrared rays
Seal Ability	Can be sealed to meet NEMA4 and IP65 standard
Warranty	Touch screen : 3 -years limited warranty
	Controller : 3 -years limited warranty

6. Touch Controller

6.1 Interface Connector : YEON-HO 10008HR-22L(22pin FPC Cable)

6.2 Input Connector CN2 : Power Connector(Molex.5267-03, YEON-HO YMW023-03R)

Pin NO.	Symbol	Description
1	GND	GND
2	GND	GND
3	Vin	Output Voltage : 5V

6.3 Interface Connector CN3 : Serial Connector(Molex.53015-0510, YEON-HO 20017WR-05)

Pin NO.	Symbol	Description
1	RX	Received Data
2	TX	Transmit Data
3	GND	GND
4	NC	No connection
5	NC	No connection

6.4 Interface Connector CN4 : USB B type Female.

7. Drawing : Please refer to Appendix1.

Note : The specification is subject to change without prior notice.